

containers in CA+PLA

> containers in cardboard (CA) + poly lactic acid (PLA)

containers in CA+PLA



Compac s.r.l.
Via Spallanzani 8/a
42024 Castelnovo di Sotto - RE - Italy
Tel. +39 0522.688.509
Fax +39 0522.688.552
www.compac.it - info@compac.it

- Containers in PLA
- Containers in APET
- Containers in CA + PLA
- Containers in CELLULOSE (PULP)
- Containers in CA + PET
- Containers in PP
- Containers in CPET
- Containers in ALUMINIUM (ALC/ALbn)


COMPAC
PACKAGING

containers in CA+PLA

> containers in cardboard (CA) + poly lactic acid (PLA)

Our containers CA+PLA are made from pure cellulose fiber coated with poly lactic acid (PLA) which makes them waterproof and greaseproof.

The containers in CA+PLA are thermo-sealable and are a paramount element of the COMPAC SYSTEM together with the tray sealers and the sealing film reels.

They are manufactured from renewable biodegradable raw materials.

Are available containers generic printing instructions for use "multilingual" in Italian/English/French/German/Spanish. On request the containers can be customized (brands and logos, texts, colours).

They can be recycled or disposed completely in industrial composting facilities.



The containers CA + PLA meet the criteria of the FSC® Certification System that ensures that the raw materials, such as pure cellulose fiber, are sourced from forests managed correctly and responsibly, confirming the environmental and social Compac respect;

The containers in CA+PLA, **BIODEGRADABLE** and **COMPOSTABLE**, are complying with the certification standards from TÜV AUSTRIA in reference to the European norm UNI EN13432.



RECYCLABLE CONTAINERS WITH PAPER – ATICELCA® 501 – level A



They belong to the Compac line *green line*

Technical properties of our containers ()

- high elasticity which make them safe from breakage during handling and transport;
- excellent resistance to aggressive chemical agents, to organic and inorganic substances (including oil, fat, etc;) and an excellent physiological behaviour (odourless, flavourless);
- suitable for reheating in microwave ovens or traditional ovens up to +200° C for 30 minutes;
- suitable for frozen food down to a minimum temperature of -40° C.



VR45PCD 500 ml



VR45GCD 1250 ml



VR45MCD 1750 ml

| Item | Series | (mm) LxBxH | ml | Pack x Pieces | L | B | H | |
|---------|--------|----------------|------|------------------|-----|-----|-----|----|
| V45PCD | P2 | 137 x 122 x 45 | 500 | 4 x 100 | 290 | 260 | 295 | 36 |
| V33GCD* | G | 192 x 140 x 33 | 500 | 4 x 100 | 400 | 300 | 300 | 24 |
| V45GCD | G | 192 x 140 x 45 | 750 | 4 x 75 | 400 | 300 | 300 | 24 |
| V75GCD* | G | 192 x 140 x 75 | 1250 | 4 x 50 | 400 | 300 | 300 | 24 |
| VS45HCD | H | 214 x 142 x 45 | 950 | 4 x 150 | 400 | 300 | 450 | 16 |
| V25LCD* | L | 232 x 192 x 25 | / | 2 x 125 | 400 | 280 | 250 | 24 |
| V45LCD | L | 232 x 192 x 45 | 1500 | 2 x 100 | 400 | 400 | 290 | 24 |
| V20MCD* | M | 262 x 192 x 20 | / | 2 x 125 | 400 | 280 | 250 | 24 |
| V45MCD | M | 262 x 192 x 45 | 1750 | 2 x 100 | 400 | 400 | 290 | 24 |
| V45XCD* | X | 322 x 192 x 45 | 2250 | 2 x 100 | 400 | 400 | 340 | 12 |

* on request

No responsibility is implied or may be linked to this catalog.

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

Compac s.r.l.
Via Spallanzani 8/a
42024 Castelnovo di Sotto - RE - Italy
Tel. +39 0522.688.509
Fax +39 0522.688.552
www.compac.it - info@compac.it

COMPANY WITH
SAFETY MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 45001 =

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV GL
= ISO 14001 =

COMPANY WITH FOOD
SAFETY SYSTEM
CERTIFIED BY DNV GL
= ISO 22000 =

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

