containers in PLA

> containers in poly lactic acid (PLA)





Via Spallanzani 8/a 42024 Castelnovo di Sotto - RE - Italy Tel. +39 0522.688.509 / +39 0522.683.873 www.compac.it - info@compac.it

- Containers in PLA
 Containers in APET
 Containers in CA + PLA
 Containers in CELLULOSE (PULP)
 Containers in CA + PET
 Containers in PP
 Containers in CPET
 Containers in ALUMINIUM (ALc/ALbn)



containers in PLA

containers in poly lactic acid (PLA)

Our containers in PLA (poly lactic acid) are manufactured from biodegradable and renewable raw materials. The containers in PLA are thermo-sealable and are a paramount element of the COMPAC SYSTEM together with the tray sealers and the sealing film reels.

The temperature range of usage is from 0° C to +40° C.

They can be recycled or disposed completely in industrial composting facilities.





The containers in PLA, BIODEGRADABLE and COMPOSTABLE, are complying with the certification standards from TÜV AUSTRIA in reference to the European norm UNI EN13432.

They belong to the Compac line green line



Technical properties of our containers (\mathbb{R}^n)

- excellent clarity;
- excellent resistance to aggressive chemical agents, to organic and inorganic substances (including oil, fat, etc;) and an excellent physiological behaviour (odourless, flavourless);
- high elasticity which make them safe from breakage during handling and transport.







GD45PT 400 ml

GD50LT 1750ml

Item	Series	(mm) LxBxH	\ ml	Pack X Pieces		B	H	
GD30PT	P1	137 x 95 x 30	250	4 x 150	400	300	210	32
GD45PT	P1	137 x 95 x 45	400	4 x 150	400	300	210	32
GD63PT	P1	137 x 95 x 63	500	4 x 150	400	300	210	32
GD45PNT	P2	137 x 120 x 45	500	4 x 150	400	300	270	24
GD65PNT	P2	137 x 120 x 65	700	4 x 150	400	300	270	24
GD82PNT	P2	137 x 120 x 82	900	4 x 125	400	300	270	24
GD25GT	G	190 x 137 x 25	500	4 x 150	400	400	290	18
GD38GT	G	190 x 137 x 38	750	4 x 125	400	400	290	18
GD50GT	G	190 x 137 x 50	1000	4 x 125	400	400	290	18
GD70GT	G	190 x 137 x 70	1250	4 x 125	400	400	290	18
GD85GT	G	190 x 137 x 85	1500	4 x 125	400	400	290	18
GD15LT	L	230 x 190 x 15	/	4 x 150	400	400	290	18
GD25LT	L	230 x 190 x 25	/	4 x 150	400	400	290	18
GD35LT	L	230 x 190 x 35	1250	4 x 150	400	400	290	18
GD50LT	L	230 x 190 x 50	1750	2 x 200	400	400	290	18
GD65LT	L	230 x 190 x 65	2250	2 x 200	400	400	290	18
GD15MT	М	260 x 190 x 15	/	4 x 120	400	400	290	18
GD25MT	М	260 x 190 x 25	/	4 x 100	400	400	290	18
GD35MT	М	260 x 190 x 35	1500	4 x 100	400	400	290	18
GD50MT	М	260 x 190 x 50	2000	2 x 150	400	400	290	18
GD65MT	М	260 x 190 x 65	2500	2 x 125	400	400	290	18
GD85MT	М	260 x 190 x 85	3000	2 x 125	400	400	290	18

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged





COMPANY WITH FOOD SAFETY SYSTEM **CERTIFIED BY DNV**

COMPANY WITH MANAGEMENT SYSTEM **CERTIFIED BY DNV** 9001 • ISO 14001 ISO 45001

