

# containers in PP

> containers in polypropylene (PP)

containers in PP



Compac s.r.l.  
Via Spallanzani 8/a  
42024 Castelnovo di Sotto - RE - Italy  
Tel. +39 0522.688.509 / +39 0522.683.873  
[www.compac.it](http://www.compac.it) - [info@compac.it](mailto:info@compac.it)

- Containers in PLA
- Containers in APET
- Containers in CA + PLA
- Containers in CELLULOSE (PULP)
- Containers in CA + PET
- Containers in PP
- Containers in CPET
- Containers in ALUMINIUM (ALC/ALbn)

**COMPAC**  
PACKAGING

# containers in PP

## > containers in polypropylene (PP)

Our containers in Polypropylene are thermo-sealable and are a paramount element of the COMPAC SYSTEM together with tray sealers and sealing film reels.

### Technical properties of the containers (🍹)

- High elasticity which make them safe from breakage during handling and transport;
- Strong seal and leak-proof;
- Excellent resistance to aggressive chemical agents, to organic and inorganic substances (including oil, fat, etc...) and an excellent physiological behaviour (odourless, flavourless);
- Suitable for reheating in the microwave at +110°C;
- Suitable for storage in the refrigerator but we advise to avoid the freezer for risk of breakage during impacts or handling.

To identify and help material sorting, our containers are marked with the following symbol: ♻️

This range is part of the Compac Line *Reline*

When collected, our containers can be recycled or incinerated.

The incineration would only produce CO2 and water vapour (H2O).



APN65T 700 ml



AG50T 1000 ml



AM50T 2000 ml

Item	Series	(mm) LxBxH	ml	CF x PZ				
APR30T	P1	95 x 136 x 30	250	4 x 125	400	300	210	32
APR45T	P1	95 x 136 x 45	400	4 x 125	400	300	210	32
APR63T	P1	95 x 136 x 63	500	4 x 125	400	300	210	32
APN45T	P2	120 x 136 x 45	500	4 x 100	400	300	270	24
APN65T	P2	120 x 136 x 65	700	4 x 100	400	300	270	24
APN82T	P2	120 x 136 x 82	900	4 x 100	400	300	270	24
AG25T	G	190 x 136 x 25	/	4 x 150	400	400	300	18
AG38T	G	190 x 136 x 38	750	4 x 125	400	400	300	18
AG50T	G	190 x 136 x 50	1000	4 x 125	400	400	300	18
AG70T	G	190 x 136 x 70	1250	4 x 125	400	400	300	18
AG85TP	G	190 x 136 x 85	1500	4 x 100	400	400	300	18
AH20T	H	208 x 136 x 20	/	4 x 90	400	300	440	16
AH38T	H	208 x 136 x 38	800	4 x 80	400	300	440	16
AH50T	H	208 x 136 x 50	1070	4 x 80	400	300	440	16
AH70T	H	208 x 136 x 70	1350	4 x 85	400	300	440	16
AH90T	H	208 x 136 x 90	1750	4 x 70	400	300	440	16
AL25T	L	230 x 190 x 25	/	2 x 200	600	400	290	16
AL35T	L	230 x 190 x 35	1250	2 x 200	600	400	290	16
AL50T	L	230 x 190 x 50	1750	2 x 200	600	400	290	16
AL65T	L	230 x 190 x 65	2250	2 x 175	600	400	290	16
AM25T	M	260 x 190 x 25	/	2 x 200	600	400	290	12
AM35T	M	260 x 190 x 35	1500	2 x 200	600	400	290	12
AM50T	M	260 x 190 x 50	2000	2 x 200	600	400	290	12
AM65T	M	260 x 190 x 65	2500	2 x 175	600	400	290	12

No responsibility is implied or may be linked to this catalog.

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

