

# containers in CA+PP

containers in CA+PP

> containers in cardboard (CA) + polypropylene (PP)



Compac s.r.l.  
Via Spallanzani 8/a  
42024 Castelnovo di Sotto - RE - Italy  
Tel. +39 0522.688.509 / +39 0522.683.873  
www.compac.it - info@compac.it

- Containers in PLA
- Containers in APET
- Containers in CA+PP
- Containers in CA + PLA
- Containers in POLPA
- Containers in CA + PET
- Containers in PP
- Containers in CPET
- Containers in ALUMINIUM (ALc/ALbn)

**CP**  
**COMPAC**  
PACKAGING

# containers in CA+PP

## > containers in cardboard (CA) + polypropylene (PP)

Our cardboard trays are produced from pure cellulose fiber coated with Polypropylene (PP) to make them waterproof and greaseproof.

The containers in CA+PP are thermo-sealable and are a paramount element of the COMPAC SYSTEM together with the tray sealers and the sealing film reels.


Are available containers generic printing instructions for use "multilingual" in Italian/English/French/German/Spanish. On request the containers can be customized (brands and logos, texts, colours).


RECYCLABLE CONTAINERS WITH PAPER – ATICELCA® 501 – level A



## Technical properties of our containers

- good mechanical properties (abrasion resistance, flexural strength, etc ... );
- high elasticity which make them safe from breakage during handling and transport;
- excellent resistance to aggressive chemical agents, to organic and inorganic substances (including oil, fat, etc;) and an excellent physiological behaviour (odourless, flavourless);
- suitable for reheating in microwave ovens or traditional ovens up to +200° C for 30 minutes;
- suitable for cooking by the consumer only if subsequent to the heat-sealing of the package with READY TO COOK food in a microwave ovens or traditional ovens up to + 200 °C for 30 minutes;
- suitable for frozen food down to a minimum temperature of -40° C.

To identify and facilitate material selective separation, our containers in cardboard (CA+PP) are marked with the following logo: 

They belong to the Compac line 

If collected, the containers can be recycled or incinerated.

Incineration would only produce usual compounds produced by paper and hydrocarbons combustion.








V45PCA 500ml



V45GCA 750ml



V45MCA 1750ml

Item	Series	(mm) LxBxH	ml	 Pack x Pieces	 L	 B	 H	
V45PCA	P2	137 x 122 x 45	500	4 x 100	290	260	295	36
V33GCA*	G	192 x 140 x 33	500	4 x 100	400	300	300	24
V45GCA	G	192 x 140 x 45	750	4 x 75	400	300	300	24
V75GCA*	G	192 x 140 x 75	1250	4 x 50	400	300	300	24
VS45HCA*	H	214 x 142 x 45	950	4 x 150	400	300	450	16
VR25LCA*	L	232 x 192 x 25	/	2 x 125	400	280	250	24
V45LCA	L	232 x 192 x 45	1500	2 x 100	400	400	290	24
VR20MCA*	M	262 x 192 x 20	/	2 x 125	400	395	250	24
V45MCA	M	262 x 192 x 45	1750	2 x 100	400	400	290	24
V45XCA*	X	322 x 192 x 45	2250	2 x 100	400	400	340	12
V48TCA*	T	260 x 160 x 48	1350	4 x 95	593	353	398	12
V50ZCA*	Z	325 x 265 x 50	3000	2 x 95	593	398	353	12

\* on request

No responsibility is implied or may be linked to this catalog.

All technical data does not have scientific value and are reported only for the purpose technical / application of the product.

Technological suitability: the product must always be verified by the user as regards the technological suitability referring to the production process, the packaging environment and the food to be packaged.

Compac s.r.l.  
Via Spallanzani 8/a  
42024 Castelnovo di Sotto - RE - Italy  
Tel. +39 0522.688.509 / +39 0522.683.873  
www.compac.it - info@compac.it



COMPANY WITH  
FOOD SAFETY SYSTEM  
CERTIFIED BY DNV  
ISO 22000

COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV  
ISO 9001 • ISO 14001  
ISO 45001

  
**COMPAC**  
P A C K A G I N G